



Conventional Charge Model	Max DC Volts	Max Start Amps Out	Max AC Amp Draw @ 480VAC	Approximate Ship Weight
24-255-30	24	42	2	20
24-375-30	24	61	3	20
24-510-30	24	83	4	22
24-600-30	24	98	4	22
24-680-30	24	111	5	22
24-765-30	24	125	5	25
24-935-31	24	152	6	49
24-1045-31	24	170	7	49
24-1190-33	24	194	8	55
24-1350-33	24	220	9	55
36-255-30	36	42	3	20
36-375-30	36	61	4	20
36-510-30	36	83	5	22
36-650-30	36	105	6	22
36-765-31	36	125	8	49
36-935-31	36	152	9	49
36-1045-31	36	170	10	49
36-1190-33	36	194	12	57
36-1275-33	36	208	13	57
36-1350-33	36	220	13	57
36-1600-33	36	260	15	59
48-255-30	48	42	3	20
48-375-30	48	61	4	20
48-500-30	48	80	6	22
48-680-31	48	111	9	46
48-800-31	48	130	11	49
48-935-33	48	152	12	57
48-1010-33	48	165	14	57
48-1190-33	48	194	15	59
48-1350-33	48	220	17	59
48-1600-32	48	260	21	90
72-255-33	72	42	5	43
72-500-33	72	80	9	46
72-980-32	72	160	18	86
72-1045-32	72	170	19	86
72-1230-32	72	200	22	90
80-255-33	80	42	6	43
80-500-33	80	80	11	46
80-615-33	80	100	13	57
80-680-33	80	111	15	57
80-800-33	80	130	17	57
80-980-32	80	160	21	86
80-1045-32	80	170	22	89
80-1230-32	80	200	26	90

All standard SB connectors included in price, SB50, SB175, SB350

Euro style connectors, Schaltbau connectors are optional

- All prices are FOB, our facility, Troy, OH, freight allowed
- Shipments to Canada, Mexico, Alaska, Hawaii, and Puerto Rico are subject to export policy
- Terms are net 30 days
- Specifications and Pricing are subject to change without notice.



Enclosure	H	W	D
Ø (5kW)	13.5"	10.5"	5.5"
1 (8kW)	21"	10"	9"
2 (16kW)	25.75"	10"	19.25"
3 (10kW)	22.5"	10.5"	9.75"